









52" - 54" Type II 20oz. Contract Wallcovering

#### PHYSICAL PROPERTIES

U.S. UNITS

**METRIC UNITS** 

Total Weight:

20.0 oz per linear yard

619 grams per linear meter451 grams per square meter

13.3 oz per square yard Nonwoven

nonwoven

Backing: Width:

52"- 54"

1.32m - 1.37m

All patterns stocked are in 30 linear yard bolts

#### DESIGN INFORMATION

VERTICAL REPEAT

**MATCH** 

Paige: 48.26 cm (19 in)

Half Drop/Reversible

### **FEDERAL SPECIFICATIONS**

Questex exceeds G.S.A Federal Specification CCC-W-408D for Type II materials using test procedures detailed in Federal Specifications CCC-T-191-B. This wallcovering passes The National Fire Protection Association NFPA286 Corner Burn Test.

#### FIRE HAZARD CLASSIFICATION RESULTS

- TESTED IN ACCORDANCE WITH ASTM E-84 TUNNEL TEST
- CLASS "A" FIRE RATED
- FLAME SPREAD 25
- SMOKE DEVELOPED 45

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

## ANTI-MICROBIAL FEATURES

Vinyl wallcoverings contain bactericides and mildew inhibitors to discourage the growth of mold and mildew under normal conditions.

# 5 YEAR WARRANTY AGAINST MANUFACTURING DEFECTS

Use only adhesives and primers as recommended by the manufacturer.

Copyright © 2016 Questex All Rights Reserved

465 Devon Park Drive, Wayne, PA 19087 USA www.wallquest.com/questex - MADE IN U.S.A.